

SICK.COM



DATA SHEET

GTB10-P4212

G10  
Photoelectric sensors

**SICK** Sensor Intelligence



Illustration may differ

# PHOTOELECTRIC SENSORS

## GTB10-P4212

### ORDERING INFORMATION

| Type        | part no. |
|-------------|----------|
| GTB10-P4212 | 1065857  |

Further device versions and accessories at [www.sick.com/G10](http://www.sick.com/G10)



### DETAILED TECHNICAL DATA

#### FEATURES

|                                 |                                |
|---------------------------------|--------------------------------|
| Functional principle            | Photoelectric proximity sensor |
| Functional principle detail     | Background suppression         |
| Dimensions (W x H x D)          | 20 mm x 50 mm x 39 mm          |
| Housing design (light emission) | Rectangular                    |
| Sensing range max.              | 20 mm ... 950 mm <sup>1)</sup> |
| Type of light                   | Visible red light              |
| Light source                    | PinPoint LED <sup>2)</sup>     |
| Light spot size (distance)      | Ø 8 mm (700 mm)                |
| Wave length                     | 625 nm                         |
| Adjustment                      | Potentiometer, 5 turns         |

<sup>1)</sup> Object with 90% remission (based on standard white, DIN 5033).

<sup>2)</sup> Average service life: 100,000 h at T<sub>u</sub> = +25 °C.

**MECHANICS/ELECTRONICS**

|                                     |                                                                          |
|-------------------------------------|--------------------------------------------------------------------------|
| Supply voltage $U_B$                | 10 V DC ... 30 V DC <sup>1)</sup>                                        |
| Ripple                              | < 5 V <sub>pp</sub> <sup>2)</sup>                                        |
| Current consumption                 | 20 mA                                                                    |
| Switching output                    | PNP                                                                      |
| Switching mode                      | Light/dark switching                                                     |
| Switching mode selector             | Selectable via light/dark selector                                       |
| Output current $I_{max}$            | ≤ 100 mA                                                                 |
| Response time                       | ≤ 500 μs <sup>3)</sup>                                                   |
| Switching frequency                 | 1,000 Hz <sup>4)</sup>                                                   |
| Connection type                     | Male connector M12, 4-pin                                                |
| Circuit protection                  | A <sup>5)</sup><br>B <sup>6)</sup><br>C <sup>7)</sup><br>D <sup>8)</sup> |
| Protection class                    | III                                                                      |
| Weight                              | 35 g                                                                     |
| Housing material                    | Plastic, ABS/PMMA                                                        |
| Enclosure rating                    | IP67                                                                     |
| Items supplied                      | Mounting bracket BEF-G10DC01                                             |
| Electromagnetic compatibility (EMC) | EN 60947-5-2                                                             |
| Ambient operating temperature       | -30 °C ... +60 °C                                                        |
| Ambient temperature, storage        | -40 °C ... +70 °C                                                        |
| UL File No.                         | NRKH.E348498 & NRKH7.E348498                                             |
| More standards                      | UL325 <sup>9)</sup>                                                      |

<sup>1)</sup> Limit values when operated in short-circuit protected network: max. 8 A.

<sup>2)</sup> May not fall below or exceed  $U_V$  tolerances.

<sup>3)</sup> Signal transit time with resistive load.

<sup>4)</sup> With light/dark ratio 1:1.

<sup>5)</sup> A =  $V_{\pm}$  connections reverse-polarity protected.

<sup>6)</sup> B = inputs and output reverse-polarity protected.

<sup>7)</sup> C = interference suppression.

<sup>8)</sup> D = outputs overcurrent and short-circuit protected.

<sup>9)</sup> Complies with the UL325 standard when used with sturdy protection hood (e.g. BEF-G10WSG, 2071960).

**SAFETY-RELATED PARAMETERS**


|                   |             |
|-------------------|-------------|
| MTTF <sub>D</sub> | 1,885 years |
| DC <sub>avg</sub> | 0 %         |

**CERTIFICATES**

|                                    |   |
|------------------------------------|---|
| EU declaration of conformity       | ✓ |
| UK declaration of conformity       | ✓ |
| ACMA declaration of conformity     | ✓ |
| Moroccan declaration of conformity | ✓ |
| China RoHS                         | ✓ |


|                                                     |   |
|-----------------------------------------------------|---|
| China Compulsory Product Certification (CCC) exempt | ✓ |
| cULus certificate                                   | ✓ |
| Photobiological safety (DIN EN 62471) certificate   | ✓ |

ADJUSTMENTS




- ⑥ Adjustment of sensing range
- ⑦ Light/dark selector



CONNECTION DIAGRAM CD-066



CHARACTERISTIC CURVE GTB10, REDLIGHT




- ① Sensing range on white, 90% remission factor
- ② Sensing range on gray, 18% remission factor
- ③ Sensing range on black, 6% remission factor

**LIGHT SPOT SIZE****SENSING RANGE DIAGRAM GTB10, REDLIGHT**

■ Sensing range

■ Sensing range max.

- ① Sensing range on white, 90% remission factor
- ② Sensing range on gray, 18% remission factor
- ③ Sensing range on black, 6% remission factor

**DIMENSIONAL DRAWING GTB10, DC, CONNECTOR**

Dimensions in mm (inch)

- ① Center of optical axis, sender
- ② Center of optical axis, receiver
- ③ Mounting hole, Ø 4.2 mm
- ④ LED indicator yellow: Status of received light beam
- ⑤ LED indicator green: power on

Further information as well as suitable accessories, example applications and downloads such as CAD dimensional models, operating instructions and software can be found at [www.sick.com/1065857](http://www.sick.com/1065857)



SICK AG  
WALDKIRCH  
GERMANY  
SICK.COM

# SICK AT A GLANCE

SICK is a leading global technology company for intelligent sensors and integrated solutions in industrial automation. Our technologies set benchmarks, making your industrial processes more efficient, safer and more sustainable – both in logistics and manufacturing operations.

SICK combines sensor intelligence with industry expertise and certified consulting services. We provide the ideal foundation for scalable as well as tailor-made automation solutions and create added value along the entire value chain. Our close partnerships with our customers are more than just a promise: Together, we optimize productivity, improve quality, protect health and safety, and help build a sustainable future. All with empathy and trust.

Since 1946, we have been developing innovative technologies with passion and a pioneering spirit. With a global network in around 40 countries, SICK has a global presence and is always close by. The company's headquarters are located in Waldkirch near Freiburg, Germany. Our customers benefit from our understanding of both local and global requirements, which enables us to deliver tailor-made solutions

**SICK**  
Sensor Intelligence